



EPOCHEMMIE CO., LTD

www.epochemmie.com

E-mail: sales@epochemmie.com pengli-epochemmie@hotmail.com plshu@sh163.net

DATA SHEET

Commodity: ACTIVATED CARBON

Type: EP-PM-S

EP-PM-S: Special higher adsorption ability with very lower impurities, Phosphoric activation
Wood based powder Activated carbon

Distinguishing feature:

- (1) Very Higher Methylene adsorption, very higher Molasses adsorption and very higher Iodine value
- (2) Very lower Heavy metal content and Almost no Zinc content, more safer for any food purification, fruit juice production etc.

Applications:

Largely used in decolorization, drinking water treatment, many food areas, sugar, juice, grape wine, pharmaceutical production, monosodium glutamate purification and so on.

Specification:

ITEM/TYPE	EP-PM-S
Methylene Blue Adsorption mg/g min	220
Molasses adsorption % min	110
Iodine Value mg/g min	1000
Moisture % max	10
PH	2-4
Iron % max	0.05
Chloride % max	0.07
Ash content % max	7
Particel size 325mesh % min passed	90%

Packing: 25kg bags or 500kg jumbo bags, or as per client's requirements

Inspection standard: the above specification is based on Chinese Government standard GB

And customer can also inspect as per American ASTM standard.

Safety

Wet activated carbon depletes oxygen from air and, therefore, dangerously low levels of oxygen maybe encountered. Whenever workers enter a vessel containing activated carbon, the vessel's oxygen content should be determined and work procedures for potentially low oxygen areas should be followed. Appropriate protective equipment should be worn. Avoid inhalation of excessive carbon dust. No problems are known to be associated in handling this material. However, dust may contain greater than 1.0% silica (quartz). Long-term inhalation of high dust concentrations can lead to respiratory impairment. Use forced ventilation or a dust mask when

necessary for protection against airborne dust exposure.

UnRegistered